

WHAT IS CLAIMED IS:

1. An elongated medical device for intraluminal manipulation during a process of magnetic resonance imaging, comprising:
  - an elongated body; and
  - an extrusion material that includes a hydrophilic polymer that incorporates a substance having a plurality of paramagnetic ions, the extrusion material being integrated with the elongated body and configured to enhance magnetic resonance visibility during said process of magnetic resonance imaging.
2. The elongated medical device of claim 1, wherein the substance having a plurality of paramagnetic ions comprises a paramagnetic metal salt.
3. ☒ The elongated medical device of claim 1, wherein the substance having a plurality of paramagnetic ions comprises a paramagnetic metal chelate.
4. The elongated medical device of claim 1, wherein the substance having a plurality of paramagnetic ions comprises a paramagnetic metal complex.
5. The elongated medical device of claim 1, wherein the substance having a plurality of paramagnetic ions comprises a gadolinium material.

FOIA b 7 - D

6. The elongated medical device of claim 1, wherein the substance having a plurality of paramagnetic ions comprises a Gadolinium diethylenetriaminepentaacetic acid material.

8. The elongated medical device of claim 1, wherein the elongated body is a tubular elongated body having an outer surface and an inner lumen surface, and wherein the extrusion material is disposed proximate the inner lumen surface.

10. The elongated medical device of claim 1, wherein the elongated body is a tubular elongated body having an outer surface and an inner lumen surface, and

wherein the extrusion material is disposed proximate the outer surface.

11. The elongated medical device of claim 1, wherein the elongated body is a tubular elongated body having an outer surface and an inner lumen surface, and wherein the extrusion material is disposed proximate both the outer surface and the inner lumen surface.

12. The elongated medical device of claim 1, further comprising a device antenna that provides active magnetic resonance imaging enhancement.

13. The elongated medical device of claim 1, further comprising a reinforcement mechanism that is configured to operate as a device antenna and provide active MRI image enhancement.

14. The elongated medical device of claim 1, wherein the extrusion material is a co-extrusion material that comprises:

a first co-extrusion component comprising a hydrophilic polymer that incorporates a substance having a plurality of paramagnetic ions, the first co-extrusion component being configured to enhance magnetic resonance visibility; and

a second co-extrusion component comprising a structural polymer, the second co-extrusion

component being configured to provide structural support.

15. The elongated medical device of claim 14, wherein the hydrophilic polymer includes a material selected from a group consisting of polyethylene oxide, polypropylene oxide, polyvinyl-pyrrolidone, hydrophilic polyurethane, polycarboxylic acids, cellulosic polymers, gelatin, maleic anhydride polymers, polyamides, a polyvinyl alcohols, polyethylene oxides and polyacrylic acid.

16. The elongated medical device of claim 14, wherein the structural polymer includes a material selected from a group consisting of nylon, PEBAX, polyurethane, polyethylene, PEEK, polyimide, polyester-amide copolymer, and polyether-amide copolymer.

17. The elongated medical device of claim 14, wherein the co-extrusion material is cross-linked so as to provide an enhanced durability.

18. The elongated medical device of claim 14, wherein the substance having a plurality of paramagnetic ions comprises a paramagnetic metal salt.

TOXEF#BESB60

20. The elongated medical device of claim 14, wherein the substance having a plurality of paramagnetic ions comprises a paramagnetic metal complex.

22. The elongated medical device of claim 14,  
wherein the co-extrusion material is integrated with  
the elongated medical device using a co-extrusion  
process wherein the first and second co-extrusion  
components are co-extruded in a striped pattern.

23. The elongated medical device of claim 14,  
wherein the co-extrusion material is integrated with  
the elongated medical device using a co-extrusion  
process wherein the first and second co-extrusion  
components are co-extruded in a spiraled pattern.

24. The elongated medical device of claim 14, wherein the substance having a plurality of paramagnetic ions comprises a gadolinium material.

25. The elongated medical device of claim 14, wherein the substance having a plurality of paramagnetic ions comprises a Gadolinium diethylenetriaminepentaacetic acid material.

26. The elongated medical device of claim 14, wherein the elongated body is a tubular elongated body having an outer surface and an inner lumen surface, and wherein the co-extrusion material is disposed proximate the inner lumen surface.

27. The elongated medical device of claim 14, wherein the elongated body is a tubular elongated body having an outer surface and an inner lumen surface, and wherein the co-extrusion material is disposed proximate the outer surface.

28. The elongated medical device of claim 14, wherein the elongated body is a tubular elongated body having an outer surface and an inner lumen surface, and wherein the co-extrusion material is disposed proximate both the outer surface and the inner lumen surface.

TO: AT: 325560

29. A method of constructing a medical device,  
comprising:

providing a medical device; and  
integrating a hydrophilic polymer that  
incorporates a substance having a plurality  
of paramagnetic ions with the medical  
device.

30. The method of claim 29, wherein the integrating  
of the hydrophilic polymer with the medical device  
comprises:

compounding the hydrophilic polymer into a  
structural polymer that is comprised by the  
medical device.

31. The method of claim 29, wherein the integrating  
of the hydrophilic polymer with the medical device  
comprises:

integrating the hydrophilic polymer with a  
balloon device.

32. The method of claim 29, wherein the integrating  
of the hydrophilic polymer that incorporates a  
substance having a plurality of paramagnetic ions  
comprises:

integrating a hydrophilic polymer that  
incorporates a paramagnetic metal salt.

TO: "PATENT" 00000000

33. The method of claim 29, wherein the integrating of the hydrophilic polymer that incorporates a substance having a plurality of paramagnetic ions comprises:

integrating a hydrophilic polymer that  
incorporates a gadolinium material to the  
medical device.

34. The method of claim 29, wherein the integrating of the hydrophilic polymer that incorporates a substance having a plurality of paramagnetic ions comprises:

integrating a hydrophilic polymer that  
incorporates a Gadolinium  
diethylenetriaminepentaacetic acid material  
to the medical device.

35. The method of claim 29, wherein the integrating of the hydrophilic polymer comprises:

extruding the hydrophilic polymer on an inner  
lumen surface of an elongated tubular  
medical device.

36. The method of claim 29, wherein the integrating of the hydrophilic polymer comprises:

extruding the hydrophilic polymer on an outer  
surface of an elongated tubular medical  
device.

TOPT-029660



37. The method of claim 29, wherein the integrating of the hydrophilic polymer comprises:

extruding the hydrophilic polymer on an outer surface and an inner lumen surface of an elongated tubular medical device.

38. The method of claim 29, wherein the integrating of the hydrophilic polymer comprises:

co-extruding onto a surface of the medical device a structural polymer in combination with a hydrophilic polymer that incorporates a substance having a plurality of paramagnetic ions.

39. The method of claim 38, wherein the co-extruding onto a surface of the medical device comprises:

co-extruding onto a surface of the medical device a structural polymer in combination with a hydrophilic polymer that incorporates a paramagnetic metal salt.

40. The method of claim 38, wherein the co-extruding onto a surface of the medical device comprises:

co-extruding onto a surface of the medical device a structural polymer in combination with a hydrophilic polymer that incorporates a gadolinium material.

TOPT-32660



46. The method of claim 45, wherein the applying the at least on final coating to the medical device comprises:

applying a lubricious coating to the medical device.

47. The method of claim 45, wherein the applying the at least on final coating to the medical device comprises:

applying a coating that contains a therapeutic agent to the medical device.

48. A material adapted to be integrated with an intraluminal medical device to enhance magnetic resonance visibility during magnetic resonance imaging, the material comprising:

a hydrophilic polymer that incorporates a substance having a plurality of paramagnetic ions.

49. The material of claim 48, wherein the substance having the plurality of paramagnetic ions comprises a paramagnetic metal salt.

50. The material of claim 48, wherein the substance having the plurality of paramagnetic ions comprises a gadolinium material.

TOGETHER

51. The material of claim 48, wherein the substance having the plurality of paramagnetic ions comprises a Gadolinium diethylenetriaminepentaacetic acid material.

52. The material of claim 48, wherein the hydrophilic polymer is a material selected from a group consisting of polyethylene oxide, polypropylene oxide, polyvinyl-pyrrolidone, hydrophilic polyurethane, polycarboxylic acids, cellulosic polymers, gelatin, maleic anhydride polymers, polyamides, a polyvinyl alcohols, polyethylene oxides and polyacrylic acid.

53. The material of claim 48, further comprising:  
a structural polymer that is co-extruded with  
the hydrophilic polymer, the hydrophilic  
polymer being configured to enhance  
magnetic resonance visibility and the  
structural polymer being configured to  
provide structural support.

54. The material of claim 53, wherein the hydrophilic polymer includes a material selected from a group consisting of polyethylene oxide, polypropylene oxide, polyvinyl-pyrrolidone, hydrophilic polyurethane polycarboxylic acids, cellulosic polymers, gelatin, maleic anhydride

TO: 0206060

polymers, polyamides, a polyvinyl alcohols, polyethylene oxides and polyacrylic acid.

55. The material of claim 53, wherein the structural polymer includes a material selected from a group consisting of nylon, PEBAX, polyurethane, polyethylene, PEEK, polyimide, polyester-amide copolymer, and polyether-amide copolymer.

56. An elongated medical device for intraluminal manipulation during a process of magnetic resonance imaging, comprising:

an elongated body; and

an extrusion material that includes a

hydrophilic polymer that incorporates a substance having a plurality of paramagnetic particles, the extrusion material being integrated with the elongated body and configured to enhance magnetic resonance visibility during said process of magnetic resonance imaging.

57. The elongated medical device of claim 56, wherein the plurality of paramagnetic particles comprise super-magnetic iron oxide.

58. The elongated medical device of claim 56, wherein the plurality of paramagnetic particles comprise dysprosium oxide.

TO: AT 825660

59. The elongated medical device of claim 56, wherein the hydrophilic polymer is a material selected from a group consisting of polyethylene oxide, polypropylene oxide, polyvinyl-pyrrolidone, hydrophilic polyurethane, polycarboxylic acids, cellulosic polymers, gelatin, maleic anhydride polymers, polyamides, a polyvinyl alcohols, polyethylene oxides and polyacrylic acid.

60. The elongated medical device of claim 56, wherein the elongated body is a tubular elongated body having an outer surface and an inner lumen surface, and wherein the extrusion material is disposed proximate the inner lumen surface.

61. The elongated medical device of claim 56, wherein the elongated body is a tubular elongated body having an outer surface and an inner lumen surface, and wherein the extrusion material is disposed proximate the outer surface.

62. The elongated medical device of claim 56, wherein the elongated body is a tubular elongated body having an outer surface and an inner lumen surface, and wherein the extrusion material is disposed proximate both the outer surface and the inner lumen surface.

Patent # 3,333,660

63. The elongated medical device of claim 56, wherein the extrusion material is a co-extrusion material that comprises:

- a first co-extrusion component comprising a hydrophilic polymer that incorporates a substance having a plurality of paramagnetic particles, the first co-extrusion component being configured to enhance magnetic resonance visibility; and
- a second co-extrusion component comprising a structural polymer, the second co-extrusion component being configured to provide structural support.

64. An elongated medical device for intraluminal manipulation during a process of magnetic resonance imaging, comprising:

- an elongated body; and
- an extrusion material that includes a hydrophilic polymer, the extrusion material being integrated with the elongated body and configured to enhance magnetic resonance visibility during said process of magnetic resonance imaging.

65. The elongated medical device of claim 64, wherein the hydrophilic polymer is a material selected from a group consisting of polyethylene oxide, polypropylene oxide, polyvinyl-pyrrolidone and

095660 325660

hydrophilic polyurethane, polycarboxylic acids, cellulosic polymers, gelatin, maleic anhydride polymers, polyamides, a polyvinyl alcohols, polyethylene oxides and polyacrylic acid.

66. The elongated medical device of claim 64, wherein the elongated body is a tubular elongated body having an outer surface and an inner lumen surface, and wherein the extrusion material is disposed proximate the inner lumen surface.

67. The elongated medical device of claim 64, wherein the extrusion material further comprises a structural polymer that is compounded into the hydrophilic polymer.

68. The elongated medical device of claim 64, wherein the elongated body is a tubular elongated body having an outer surface and an inner lumen surface, and wherein the extrusion material is disposed proximate the outer surface.

69. The elongated medical device of claim 64, wherein the extrusion material is a co-extrusion material that comprises:

- a first co-extrusion component comprising a hydrophilic polymer, the first co-extrusion component being configured to enhance magnetic resonance visibility; and

Patent 6,329,660



a second co-extrusion component comprising a structural polymer, the second co-extrusion component being configured to provide structural support.

70. The elongated medical device of claim 64, further comprising a reinforcement mechanism that is configured to operate as a device antenna and provide active MRI image enhancement.

71. A method of constructing a medical device with enhanced magnetic resonance visibility, comprising:  
providing a medical device; and  
integrating a material that comprises a hydrophilic polymer with the medical device.

72. The method of claim 71, wherein the integrating the material with the medical device comprises:  
compounding the material with a structural polymer that is comprised by the medical device.

73. The method of claim 71, wherein the integrating of the hydrophilic polymer with the medical device comprises:  
integrating the hydrophilic polymer with a balloon device.

Patent 8,255,660

extruding the material on an inner lumen surface  
of an elongated tubular medical device.

extruding the material on an outer surface of an elongated tubular medical device.

co-extruding onto a surface of the medical device a structural polymer in combination with a hydrophilic polymer.

co-extruding on an inner lumen surface of an elongated tubular medical device.

co-extruding on an outer surface of an elongated tubular medical device.

79. A method of utilizing a medical device having enhanced magnetic resonance imaging visibility, comprising:

providing a medical device that incorporates an  
integrated hydrophilic polymer;  
causing the hydrophilic polymer to absorb fluid;  
utilizing the medical device within an  
intraluminal environment within a patient  
during a process of magnetic resonance  
imaging.

80. The method of claim 79, wherein causing the  
hydrophilic polymer to absorb fluid comprises:

pre-soaking at least one portion of the medical  
device.

81. The method of claim 79, wherein causing the  
hydrophilic polymer to absorb fluid comprises:

introducing at least one portion of the medical  
device to a fluid environment within a patient.

82. The method of claim 79, wherein providing a  
medical device that incorporates an integrated  
hydrophilic polymer further comprises:

providing a medical device that incorporates an  
integrated hydrophilic polymer that  
includes a substance having a plurality of  
paramagnetic ions.

83. The method of claim 82, wherein causing the  
hydrophilic polymer to absorb fluid comprises:

FOIA b 7 - DEX

pre-soaking at least one portion of the medical device.

84. The method of claim 82, wherein causing the hydrophilic polymer to absorb fluid comprises:

introducing at least one portion of the medical device to a fluid environment within a patient.

10/22/2014 10:56:00